

	4CX Disc	VCX Disc		ECX Disc		Hyalite	Hyalite ES
Wheel size	700c	700c (CL)	700c (TU)	700c (CL)	700c (TU)	700c	700c
Weight	1355g	1720g	1610g	1765g	1740g	1520g	1575g
FT	620g	810g	745g	805g	800g	700g	705g
RR	735g	910g	865g	960g	940g	820g	870g
Spoke Count	20/20			24/24		20/20	24/24
Spoke Type	Bladed CX-Ray	Bladed CX-Speed				Round Laser	
Rim Depth	42mm	31mm	28mm	31mm	28mm	23mm	23mm
Max width	26mm	22mm				25mm	
Brake track width (external)	22mm					25mm	
Brake track width (internal)	n/a	17mm	n/a	17mm	n/a	22mm	
Rim Material	Carbon Tubular	Alloy Clincher (Made in the US)	Alloy Tubular (Made in the US)	Alloy Clincher (Made in the US)	Alloy Tubular (Made in the US)	Alloy Clincher (Made in the US)	
Hubset	XST with T2 high engagement			XR		XST with T2 high engagement	XR
Bearings	Steel						
Freehub Material	CNC Machined Titanium			Forged 6061 T6 Alloy		CNC Machined Titanium	Forged 6061 T6 Alloy
Freehub Compatible	Shimano/SRAM 10/11 or SRAM XD 1 x 11						
Brake Type	Center Lock			6-Bolt		Center Lock	
QR's	RP6.0 Internal	RP5.5 Internal					
Front hub Compatibility	15mm TA/ 9mm QR, 12mm TA			15mm TA / 9mm QR		15mm TA/ 9mm QR, 12mm TA	
Rear hub Compatibility	142mm TA/ 135mm QR						
Includes	QR set	Rim Strips & QR set	QR set	Rim Strips & QR set	QR set	Taped for tubeless, Valves & QR's where applicable	